

Semi-Rigid & Flexible Cable Assembly 0.047", 0.085", 0.141" & 0.250" Type

Withwave's Semi-Rigid and Flexible Cable Assemblies have different types of cable outer diameters with 0.047", 0.085", 0.141" & 0.250" for various kinds of application according to customer's requirement.

■ Features

- Center Conductor : Silver plated Copper wire
- Dielectric core : Solid PTFE
- Jacket : Copper tubing, Tin-plated



■ Specification (Semi-Rigid type)

Scope	Specification	SR047	SR085	SR141
Physical	Center Conductor (mm)	0.29	0.51	0.92
	Dielectric (mm)	0.92	1.68	2.98
	Jacket (mm)	1.19	2.20	3.58
Electrical	Impedance (Ohm)		50	
	Operation Freq.(GHz)	20	20	20
	Velocity of propagation(%)		69.5	
	Capacitance (pF/ft)	32	32	29.9
	Shielding Effectiveness (dB)		100	
Mechanical & Environmental	Weight (g/M)	5.7	20.2	46.7
	Operation Temperature		-40~ +125℃	

■ Specification (Semi-Flexible type)

Scope	Specification	SF047	SF085	SF141
Physical	Center Conductor	0.29	0.54	0.95
	Dielectric	0.92	1.68	2.98
	Jacket	1.19	2.18	3.58
Electrical	Impedance (Ohm)		50	
	Operation Freq.(GHz)	20	20	20
	Velocity of propagation(%)		69.5	
	Capacitance (pF/ft)	32	32	20
	Shielding Effectiveness (dB)		100	
Mechanical & Environmental	Weight (g/M)	5.7	16.0	45
	Operation Temperature		-40~ +125℃	

Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type

withwave


Versatile RF & MW Test Solutions

■ Test Result

SF047 cable Assembly


Part No: SF047-SM1SM1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.1 meter



Part No: SF047-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type

withwave

Versatile RF & MW Test Solutions

■ Test Result

SR047 cable Assembly


Part No: SR047-SM1SM1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.1 meter



Part No: SR047-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type

withwave


Versatile RF & MW Test Solutions

■ Test Result

SF085 cable Assembly


Part No: SF085-SM1SM1-0.2M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.2 meter



Part No: SF085-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type

withwave
Versatile RF & MW Test Solutions

■ Test Result

SR085 cable Assembly


Part No: SR085-SM1SM1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.1 meter



Part No: SR085-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type


withwave
Versatile RF & MW Test Solutions

■ Test Result

SF141 cable Assembly


Part No: SF141-SM1SM1-0.2M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.2 meter



Part No: SF141-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type

withwave
Versatile RF & MW Test Solutions

■ Test Result

SR141 cable Assembly


Part No: SR141-SM1SM1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Male)
- Cable Length : 0.2 meter



Part No: SR141-SF1SF1-0.1M

- Frequency : DC to 6 GHz
- Connector : SMA(Female)
- Cable Length : 0.1 meter



Semi-Rigid & Flexible Cable Assembly 047", 085", 141" & 250" Type


withwave
Versatile RF & MW Test Solutions

■ Test Result

SF250 cable Assembly


Part No: SF250-SM1SM1-0.2M

- Frequency : DC to 3 GHz
- Connector : SMA(Male)
- Cable Length : 0.2 meter




Part No: SF250-NM1NM1-0.2M

- Frequency : DC to 3 GHz
- Connector : N-type(Male)
- Cable Length : 0.2 meter




■ Selection Guide


SR085 – SMSF – 1M



Cable Type	Connector Type	Cable Length
SR047 SR085 SR141 SF047 SF085 SF141 SF250	SM : SMA Male SF : SMA Female NM : N-Type Male NF : N-Type Female	Unit : Meter




Cable Specification




Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			32 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.29±0.02	SPCW	
	2 Dielectric	0.92±0.03	PTFE	
	3 Outer Shield	1.19±0.03	TC	
Mechanical And Environmental Performance	Weight (g/m)			5.7
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.75	66.5	
	1000	1.09	47.0	
	5000	2.60	21.0	
	10000	3.75	15.3	
	20000	5.51	10.5	

Cable Specification




Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			32 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.51±0.005	SPCW	
	2 Dielectric	1.68±0.030	PTFE	
	3 Outer Shield	2.20±0.025	TC	
Mechanical And Environmental Performance	Weight (g/m)			20.2
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.49	180.0	
	1000	0.72	130.0	
	5000	1.64	54.0	
	10000	2.62	35.0	
	20000	4.27	20.0	

Cable Specification




Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			29.9 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.92±0.005	SPCW	
	2 Dielectric	2.98±0.050	PTFE	
	3 Outer Shield	3.58±0.050	TC	
Mechanical And Environmental Performance	Weight (g/m)			46.7
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.26	600.0	
	1000	0.39	450.0	
	5000	0.95	180.0	
	10000	1.48	120.0	
	20000	2.30	70.0	

Cable Specification




Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			32 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.29±0.005	SPCW	
	2 Dielectric	0.92±0.050	PTFE	
	3 Outer Shield	1.19±0.050	TC	
Mechanical And Environmental Performance	Weight (g/m)			5.7
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.75	17.7	
	1000	1.09	11.9	
	5000	2.60	5.1	
	10000	3.75	3.5	
	20000	5.51	-	

■ Cable Specification



Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			32 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.54±0.005	SPC	
	2 Dielectric	1.68±0.050	PTFE	
	3 Outer Shield	2.18±0.025	TC	
Mechanical And Environmental Performance	Weight (g/m)			16.0
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.49	37.4	
	1000	0.72	25.2	
	5000	1.64	10.8	
	10000	2.62	7.4	
	20000	4.27	-	

Cable Specification



Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			20 GHz
	Impedance (Ohm)			50 ± 2
	Capacitance			29.9 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	0.95±0.013	SPC	
	2 Dielectric	2.98±0.050	PTFE	
	3 Outer Shield	3.58±0.050	TC	
Mechanical And Environmental Performance	Weight (g/m)			45.0
	Operating Temperature Range (°C)			-40~+125
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.26	600	
	1000	0.72	450	
	5000	1.64	180	
	10000	2.62	120	
	20000	4.27	70	

Cable Specification



Scope	Item			Specification
Electrical Properties	Operating Frequency Range (GHz) : Max			18 GHz
	Impedance (Ohm)			50 ± 3
	Capacitance			29.9 pF/ft
	Velocity Propagation			69.5 %
Material & Construction	Structure	Size (mm)	Material	
	1 Center Conductor	1.65±0.03	SPC	
	2 Dielectric	5.35±0.05	PTFE	
	3 Outer Shield	6.30±0.05	TC	
	4 Jacket(Optional)	7.10±0.05	PVC/PE	
Mechanical And Environmental Performance	Weight (g/m)			114.0
	Operating Temperature Range (°C)			-55~+200
Attenuation values	Freq MHz	dB /M	Average power (Watts)	
	500	0.15	1,800	
	2000	0.37	1,050	
	5000	0.52	435	
	10000	1.08	282	